



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1015109	19	3/4	26	1,02	10	150	30	450	0,30	0,20	120	400
1015222	25	1	33	1,30	10	150	30	450	0,46	0,31	120	400
1015338	32	1-1/4	42	1,65	10	150	30	450	0,78	0,52	120	400
1143786	38	1-1/2	47	1,85	10	150	30	450	0,77	0,52	120	400
1457462	40	1-37/64	53,5	2,11	10	150	30	450	1,17	0,79	120	400
1088335	51	2	61	2,40	10	150	30	450	1,12	0,75	120	400
1119389	63,5	2-1/2	75,5	2,97	10	150	30	450	1,71	1,15	120	400
1143760	76	3	87	3,43	10	150	30	450	1,79	1,20	120	400
1101021	90	3-35/64	106	4,18	10	150	30	450	3,13	2,10	120	400
1141597	102	4	120	4,73	10	150	30	450	4,08	2,74	120	400



EN

Water discharge hose

Application: softwall discharge hose for water, non corrosive fluids and compressed air; used in construction sites, industries and agriculture.

Temperature: from -35°C (-31°F) to +70°C (+158°F).

Construction

Tube: black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth, (wrapped finish) synthetic rubber, weathering and ozone resistant.

Branding: continuous green spiral stripe "IVG Water (family logo)...".

Also available upon request: 1. Different diameters 2. Yellow or blue hose cover 3. Different working pressures.

CN

排水管

应用范围: 适用于水或不具腐蚀性的液体和压缩空气; 适用于建筑工地, 工业和农业领域等

温度范围: -35° C (-31° F) 到 +70° C (+158° F)

软管结构

内层: 黑色, 光滑, 合成橡胶

加强层: 高强度合成线绳

外层: 黑色, 光滑, 合成橡胶, 耐侵蚀, 耐氧化

商标: 连续绿色缠绕状标记 "IVG Water (公司商标)..."

可选择项: 1. 不同口径 2. 黄色或蓝色外层 3. 各种工作压力

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).