



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1453777	15	19/32	25,5	1,00	10	150	30	450	0,53	0,36	75	3,0	0,9	60	200
1452088	22	7/8	32,5	1,28	10	150	30	450	0,71	0,48	110	4,3	0,9	60	200
1485962	25	1	36	1,42	10	150	30	450	0,87	0,58	125	4,9	0,9	60	200
1452070	28	1-7/94	39	1,54	10	150	30	450	0,95	0,64	140	5,5	0,9	60	200
1452096	30	1-3/16	41	1,62	10	150	30	450	1,01	0,68	150	5,9	0,9	60	200
1452436	35	1-3/8	46	1,81	10	150	30	450	1,14	0,77	175	6,9	0,9	60	200
1452100	40	1-37/64	51	2,01	10	150	30	450	1,28	0,86	200	7,9	0,9	60	200
1452118	43	1-11/16	54	2,13	10	150	30	450	1,36	0,91	215	8,5	0,9	60	200
1452126	51	2	63	2,48	10	150	30	450	1,85	1,24	255	10,0	0,9	60	200
1452428	76	3	89	3,51	10	150	30	450	3,03	2,04	455	17,9	0,9	60	200
1475789	90	3-35/64	104	4,10	10	150	30	450	4,04	2,71	540	21,3	0,9	60	200



EN

Sanitary hose for the toilets in the trains

Standards: EN 45545 HL3 R22 and R23; BS 6853 Cat. Ia Int. Cat. Ia Ext.

Application: hardwall hose designed to convey water in the sanitary connections of trains toilets.

Temperature: from - 30°C (-22°F) to +70°C (+158°F).

Construction

Tube: black, smooth, special synthetic rubber compound.

Reinforcement: high strength synthetic cord plus embedded steel helix wire.

Cover: black, smooth (wrapped finish) special synthetic rubber compound, ozone, ageing, weathering and oil mist resistant.

Branding: green transfer tape "Rail (family logo) Sanitary Premium EN 45545 HL3 R22/R23 - BS 6853".

Also available upon request: 1. According to DIN 5510-2 S3/SR2/ST2. 2. Sanitary Star with odourless and taste free IIR tube 3. Different diameters.

CN

火车卫生管

质量标准: EN 45545 HL3 R22 and R23; BS 6853 Cat. Ia Int. Cat. Ia Ext.

应用范围: 硬壁软管，应用于列车卫生间送水。

温度范围: - 30° C (-22° F) 到 +70° C (+158° F)。

软管结构

内层: 黑色，光滑，特殊合成橡胶。

加强层: 高强度合成线绳及嵌入式螺旋钢丝。

外层: 黑色，光滑(表面布纹)特殊合成橡胶，耐臭氧、耐老化、耐气候，耐油雾。

商标: 绿色条带: "Rail (family logo) Sanitary Premium EN 45545 HL3 R22/R23 - BS 6853".

可选择项: 1. 根据DIN 5510-2 S3/SR2/ST2 标准生产的管道。
 2. Sanitary Star管道，IIR内胶无嗅无味。 3. 不同口径。