



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1450719	6	1/4	16	0,63	10	150	50	750	0,23	0,16	60	200
1438212	8	5/16	18	0,71	10	150	50	750	0,27	0,18	60	200
1438441	10	25/64	22	0,87	10	150	50	750	0,41	0,28	60	200
1432826	12	15/32	24	0,95	10	150	50	750	0,46	0,31	60	200
1449869	13	1/2	26	1,02	10	150	50	750	0,51	0,34	60	200
1414844	15	19/32	27	1,06	10	150	50	750	0,54	0,36	60	200
1438581	16	5/8	29	1,14	10	150	50	750	0,59	0,40	60	200
1436066	19	3/4	33	1,30	10	150	50	750	0,76	0,51	60	200
1432419	20	25/32	34	1,34	10	150	50	750	0,79	0,53	60	200
1432427	22	7/8	37	1,46	10	150	50	750	0,94	0,63	60	200
1449451	25	1	39,5	1,56	10	150	50	750	0,97	0,65	60	200
1437127	28	1/7-64	47	1,85	10	150	50	750	1,54	1,04	60	200
1480308	32	1-1/4	49	1,93	10	150	30	450	1,44	0,97	60	200
1499556	38	1-1/2	57	2,25	10	150	30	450	1,95	1,31	60	200


EN

Compressed air hose

Standards: NF F11-380:2017/CAT.2. EN 45545-2:15 HL3 R22 and R23; BS 6853 Cat. Ia Int. Cat. Ia Ext.

Application: softwall hose designed to convey compressed air in rail carriages and locomotive systems according to the standard NF F11-380:2017/CAT.2. Fire resistant, with low toxicity and smoke emission. Halogen free.

Temperature: from -30°C (-22°F) to +70°C (+158°F).

Construction

Tube: black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), synthetic rubber, weathering, ozone, oil and fire resistant.

Branding: continuous white band "IVG/quarter and year of production - I.D. - NF F 11 - 380 CAT 2 - batch n°".

Also available upon request: 1. Different diameters.

CN

压缩空气管

质量标准: NF F11-380:2017/CAT.2. EN 45545-2:15; BS 6853, Cat. Ia Int. Cat. Ia Ext.

应用范围: : 软壁软管, 用于输送火车机车与车辆之间压缩空气。符合 NF F11-380:2017/CAT.2. 标准。耐火、低毒、低烟。无卤素。

温度范围: -30° C (-22° F) 到 +70° C (+158° F)。

软管结构

内层: 黑色, 光滑合成橡胶。

加强层: 高强度合成线绳。

外层: 黑色, 光滑(表面布纹), 合成橡胶、耐老化、臭氧、耐油, 防火。

商标: 连续白色条纹 "IVG/季度和年度-内径- NF F 11 -380 CAT 2 - 批次号"。

可选择项: 1. 不同口径。