



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1237390	51	2	71	2,80	15	225	60	900	2,82	1,90	500	19,7	0,9	12	40
1308661	76	3	96	3,78	15	225	45	675	4,17	2,80	850	33,5	0,9	12	40
1237403	102	4	135,5	5,34	15	225	60	900	8,51	5,72	1200	47,3	0,9	12	40
1237489	127	5	163	6,42	15	225	60	900	11,60	7,80	1670	65,8	0,9	12	40
1237500	152	6	193,5	7,62	15	225	60	900	17,64	11,85	2000	78,8	0,9	12	40
1237527	203	8	251,50	9,91	15	225	60	900	28,39	19,07	2800	110,3	0,9	12	40


EN

Ship to ship petroleum products loading and unloading hose according to EN 1765 and BS 1435

Standards: EN 1765:2004 type S 15 – BS 1435 type S 15. RINA approved n. MAC338724CS.

Application: hardwall hose used for the suction and discharge of petroleum products with an aromatic content up to 50% in ship to ship loading and unloading operations. Realized with built-in fittings. Available also with swaged-on fittings.

Not suitable for SubMarine – Offshore Moorings applications.

Temperature: from -20°C (-4°F) to +82°C (+180°F).

Construction

Tube: black, smooth, synthetic rubber, suitable for aromatic content up to 50%.

Reinforcement: high strength synthetic cord plus steel helix wire.

Cover: black, smooth (wrapped finish), synthetic rubber resistant to weathering, oil and sea water.

Electrical Resistance: electrically discontinuous.

Branding: continuous yellow stripe "On Shore Filicudi Electrically Discontinuous EN 1765 S 15 - logo IVG" and marking according to specifications.

CN

船间石油吸排管

质量标准: EN 1765:2004 type S 15 – BS 1435 type S 15. RINA 认证 n. MAC338724CS.

应用范围: 导电硬壁软管，用于船间装卸作业中抽吸和输送芳烃含量高 达50% 的石油产品；可以提供扣压式或建入式接头。

温度范围: -20° C (-4° F) 到 +82° C (+180° F)。

软管结构

内层: 黑色，光滑，合成橡胶，耐50% 的芳烃。

加强层: 高强度合成线绳，加螺旋钢丝骨架。

外层: 黑色，光滑（表面布纹），合成橡胶，抗老化、耐油和海水。

电阻性: 导电。

商标: 连续黄色条纹 "On Shore Filicudi Electrically Discontinuous EN 1765 S 15 - logo IVG 商标"，可按照不同规格标记。