



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft	
1200746	13	1/2	26	1,02	10	150	40	600	0,62	0,42	70	2,8	0,9	60	200	
1349520	19	3/4	33	1,30	10	150	40	600	0,91	0,61	100	4,5	0,9	60	200	
1356089	25	1	38	1,50	10	150	40	600	1,04	0,70	125	4,9	0,9	60	200	
1348760	32	1-1/4	46	1,81	10	150	40	600	1,34	0,90	160	6,3	0,9	60	200	
1333445	38	1-1/2	52	2,05	10	150	40	600	1,51	1,02	190	9,9	0,9	60	200	
1333453	51	2	66	2,60	10	150	40	600	2,17	1,46	280	13,6	0,9	60	200	
1354256	63,5	2-1/2	78,5	3,09	10	150	40	600	2,64	1,77	350	17,7	0,9	60	200	
1339788	76	3	94	3,70	10	150	40	600	3,72	2,50	450	17,7	0,9	60	200	
1336525	102	4	120	4,73	10	150	40	600	5,09	3,42	600	23,6	0,9	60	200	



EN

Chemical and petroleum suction and discharge, PE-X tube.

Application: hardwall hose suitable for handling a wide range of chemicals, petroleum products and oils. Normally installed on tank trucks and discharge platforms in chemical and oil industries.

Temperature: -40°C(-40°F)to+80°C(+176°F) depending on medium.

Construction

Tube: black, smooth, cross-linked polyethylene (PE-X). Chemical resistance according to IVG chemical resistance chart. For temperature exceeding 50°C contact IVG.

Reinforcement: high strength synthetic cord, steel helix wire and antistatic copper wire.

Cover: green, smooth (wrapped finish), EPDM rubber resistant to chemicals, weathering and ozone.

Branding: continuous blue/white stripe "IVG Chem PE-X (family logo)...".

Also available upon request: 1. Supertop pe-x/ll/bv with a non food quality white pe-x tube 2.Different diameters.

CN

多用途化学品和石油产品吸排管, PE-X内胶

应用范围:硬壁胶管, 广泛用于输送各种化学物质, 石油产品及油类。广泛用于液体罐车, 化工和石油工业的卸货平台上。

温度范围: -40° C (-40° F) 到 +80° C (+176° F), 视介质而定。

软管结构

内层: 黑色, 光滑, 交联聚乙烯(PE-X)。化学品适应性请参照IVG化学物质表, 当输送温度高于50°C请与我方联系。

加强层: 高强力合成线绳, 螺旋钢丝及抗静电铜丝。

外层: 绿色, 光滑(表面布纹), EPDM 橡胶。耐化学物质, 抗老化, 耐臭氧。

商标: 连续蓝/白色条纹 "IVG Chem (公司商标)..."

可选择项: 1. 非食品级白色Supertop pe-x/11/bv管。2. 不同口径。



Above technical data are referring to applications at room temperature (+20°C).

IVG Colbachini is not liable for the use that differs from what is confirmed in their catalogues, product sheets, offers, order confirmations and contained recommendations. For a correct use refer to "Recommendations for the selection, storage, use and maintenance of rubber hoses" by Assogomma, available on www.ivgspa.it.

With the aim to improve the product, IVG reserves the right to modify the hose specifications without giving any prior notice.

data sheet date/技术参数日期: 31/05/2024