



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1262270	13	1/2	27	1,06	10	150	40	600	0,58	0,39	60	2,4	0,9	120	400
1210947	19	3/4	32	1,26	10	150	40	600	0,67	0,45	85	3,3	0,9	120	400
1067591	25	1	38	1,50	10	150	40	600	0,87	0,59	115	4,5	0,9	120	400
1025325	32	1-1/4	46,5	1,83	10	150	40	600	1,16	0,78	145	5,7	0,9	121	397
1094939	38	1-1/2	51	2,01	10	150	40	600	1,23	0,83	180	7,1	0,9	120	400
1348892	51	2	65	2,56	10	150	40	600	1,77	1,19	245	9,7	0,9	120	400
1348906	76	3	92	3,62	10	150	40	600	2,99	2,01	390	15,4	0,9	120	400
1211064	102	4	120	4,73	10	150	40	600	4,65	3,12	555	21,9	0,9	120	400



EN

Suction and discharge of aggressive chemicals, EPR quality

Application: hardwall hose designed to handle a wide range of chemical products, acids, bases, aldehydes and ketones. It is specially recommended to convey industrial waters and for use in water purification systems.

Temperature: -40°C(-40°F) +120°C(+248°F) depending on medium.

Construction

Tube: black, smooth, antistatic EPR rubber. Chemical resistance according to IVG chemical resistance chart. For temperature exceeding 50°C contact IVG.

Reinforcement: high strength synthetic cord plus steel helix wire.

Cover: black, antistatic, smooth (wrapped finish), EPR rubber, resistant to chemical products, abrasion, weathering and ozone.

Branding: continuous violet stripe "IVG Chem (family logo)...".

Also available upon request: 1.Different diameters 2.Different colour covers 3.Different working pressures.

CN

化学溶剂吸排管/EPR

应用范围: 硬壁胶管，广泛用于输送各种化学溶剂，酸，碱，乙醛及酒精。特别适用于工业排水及水净化系统。

温度范围: -40° C(- 40° F) 到 +120° C(+248° F), 视介质而定。

软管结构

内层: 黑色，光滑，EPR橡胶。化学品适应性请参照IVG化学物质表，当输送温度高于50°C请与我方联系。

加强层: 高强度合成线绳及螺旋环绕钢丝。

外层: 黑色，抗静电，光滑(表面布纹)，EPR 橡胶。耐化学物质 耐磨损，抗老化，耐臭氧。

商标: 连续紫色条纹“IVG Chem (公司商标)...”。

可选择项: 1. 不同口径 2. 不同外胶颜色 3. 不同工作压力。