



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1034901	19	3/4	29	1,14	10	150	40	600	0,51	0,34	121	397
1229710	25	1	38	1,50	10	150	40	600	0,86	0,58	120	400
1034871	32	1-1/4	44	1,73	10	150	40	600	0,94	0,63	121	397
1065572	38	1-1/2	48	1,89	10	150	40	600	0,93	0,63	120	400
1229737	51	2	69	2,72	10	150	40	600	2,23	1,50	120	400
1229745	63,5	2-1/2	81	3,19	10	150	40	600	2,60	1,75	120	400
1175505	76	3	95	3,74	10	150	40	600	3,42	2,30	120	400
1090291	102	4	121	4,77	10	150	40	600	4,47	3,00	120	400



EN

Chemical and solvents discharge, Viton® tube

Application: softwall hose mainly used in the petrochemical industry for the delivery of a wide range of chemical products with high concentrations, combustible aromatics, hot oils and solvents. Especially designed for the petrochemical industry.

Temperature: -25°C(-13°F) +120°C(+248°F) depending on medium.

Construction

Tube: black, smooth, Viton® (FKM) rubber. Chemical resistance according to IVG chart. For temperature exceeding 50°C contact IVG.

Reinforcement: high strength synthetic cord.

Cover: black, smooth, (wrapped finish), CR rubber, resistant to abrasion, weathering, ozone and oils.

Branding: continuous violet stripe "IVG Chem (family logo)...".

Also available upon request: 1. Different diameters 2. Different working pressures.

CN

化学溶剂输送管/Viton

应用范围: 软壁胶管，可广泛用于石油化工行业输送高浓度的化学品，易燃性芳香族化合物，热油和溶剂等。专门设计用于石化行业。

温度范围: -25° C (-13° F) 到+120° C (+248° F), 视介质而定。

软管结构

内层: 黑色，光滑，氟橡胶 (FKM)。化学品适应性请参照IVG化学物质表，当输送温度高于50°C请与我方联系

加强层: 高强度合成线绳。

外层: 黑色，光滑 (表面布纹)，CR橡胶，耐磨，抗老化，耐臭氧和耐油。

商标: 连续紫罗兰色条纹 "IVG Chem (公司商标)...".

可选择项: 1. 不同口径 2. 不同工作压力。