



code	inside diameter		burst pressure		weight nominal		bending radius		length max	
	mm	inch	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
1386530	25	1	2	30	0,53	0,35	100	3,9	60	200
1391526	32	1-1/4	2	30	0,65	0,44	130	5,1	60	200
1390902	38	1-1/2	2	30	0,74	0,50	150	5,9	60	200
1383620	40	1-37/	2	30	0,77	0,52	160	6,3	60	200
1383639	45	1-49/64	2	30	0,86	0,58	170	6,7	60	200
1378392	51	2	2	30	1,06	0,71	180	7,1	60	200
1383612	58	2-9/32	2	30	1,20	0,81	190	7,5	60	200
1383590	63,5	2-1/2	2	30	1,30	0,87	200	7,9	60	200
1383604	76	3	2	30	1,46	0,98	250	9,9	60	200
1384856	90	3-35/64	2	30	1,71	1,15	330	13,0	60	200
1384864	102	4	2	30	2,05	1,38	410	16,2	60	200
1385429	127	5	2	30	2,58	1,73	560	22,1	60	200
1393952	152	6	2	30	3,18	2,14	680	26,8	60	200
1396757	203	8	2	30	3,69	2,48	995	39,2	60	200


EN

Marine wet exhaust gas hose

Standards: Lloyd's Register Rules and Regulations for the Classification of Special Service Craft: Type Approval Certificate LR2003377TA. Homologation VTT according to Nordic Boat Standard MC9.

Application: hardwall corrugated hose, flexible and lightweight, used to convey wet gas exhaust mixed with water in pleasure boats.

Temperature: from -30°C (-22°F) to +100°C(+212°F).

Construction

Tube: black, smooth, synthetic rubber, gas exhaust resistant

Reinforcement: high strength synthetic cord plus steel helix wire.

Cover: black, corrugated (wrapped finish), flame retardant synthetic rubber, weathering resistant.

Branding: continuous white/blue stripe "Boat (family logo) ETNA - MARINE WET GAS EXHAUST - LLOYD'S N° LR2003377TA - FIRE RESISTANT - ACCORDING MK9 VTT REP 761/97 (IVG LOGO)".

RU

Рукав для отвода выхлопных газов, смешанных с морской водой

Нормативы: Lloyd's Register Rules and Regulations for the Classification of Special Service Craft: Type Approval Certificate LR2003377TA. Договор NORDIC BOAT Standard MC9 утверждённый VTT.

Применение: гофрированный напорно-всасывающий гибкий и лёгкий рукав для отвода выхлопных газов, смешанных с охлаждающей водой, предназначен для прогулочных катеров.

Температура: от -30 до +100°C.

Конструкция

Внутренний слой: чёрный, гладкий из синтетического каучука, устойчивый к выхлопным газам.

Усиление: высокопрочный синтетический корд, встроенная стальная спираль.

Покрытие: чёрное, гофрированное (с отпечатком текстильного бандажа), из синтетического невосгорающегося каучука, устойчивое к атмосферным воздействиям.

Маркировка: сине/белая маркировочная лента "Boat (логотип сферы применения) ETNA - MARINE WET GAS EXHAUST - LLOYD'S N° LR2003377TA - FIRE RESISTANT - ACCORDING MK9 VTT REP 761/97 (ЛОГОТИП IVG)".

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).