



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1307703	10	25/64	18	0,71	30	450	90	1350	0,22	0,15	120	400
1096451	13	1/2	21	0,83	30	450	90	1350	0,26	0,17	120	400
1456784	19	3/4	28	1,10	30	450	90	1350	0,40	0,27	120	400
1456792	25	1	35	1,38	30	450	90	1350	0,59	0,39	120	400
1458540	32	1-1/4	44	1,73	30	450	90	1350	0,91	0,61	120	400
1458558	38	1-1/2	51	2,01	30	450	90	1350	1,17	0,78	120	400
1479652	50	2	66	2,60	30	450	90	1350	1,82	1,22	120	400



**EN**

## Multipurpose hose suitable for use in agriculture, car washes, industrial vehicles, compressors

**Standards:** flame retardant cover compound according to ASTM C-542.

**Application:** softwall hose of excellent quality, versatile, easy to handle and flexible, for delivery of compressed air, hot water, water mixed with additives such as fire fighting powders, insecticides, car washing shampoo, cooling water mixed with antifreeze.

**Temperature:** from -30°C (-22°F) to +100°C (+212°F).

**Construction**

**Tube:** black smooth synthetic rubber.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth (wrapped finish) synthetic rubber, self extinguishing, oils, weathering and ozone resistant.

**Branding:** yellow brand "IVG water(family logo) Luwas/30...".

**Also available upon request:** 1. Different diameters.

**CN**

## 多用途消防水管

**质量标准:** 外胶防火符合ASTM C-542 标准

**应用范围:** 优质软壁管，多用途，柔韧轻便易操作，用于输送压缩空气，热水，水和添加剂，例如救火粉剂，杀虫剂，洗车香波混合，冷却水混合防冻液。广泛应用于农业，洗车，工业车辆和压缩机等领域

**温度范围:** -30° C (-22° F) 到 +100° C (+212° F)

**软管结构**

**内层:** 黑色，光滑，合成橡胶

**加强层:** 高强度合成线绳

**外层:** 黑色，光滑合成橡胶，阻燃，耐油，耐臭氧，耐老化

**商标:** 黄色商标 "IVG water (公司商标) Luwas/30..."

**可选择项:** 1. 不同口径