




code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
1900540	9	23/64	16	0,63	10	150	25	375	0,20	0,13	60	2,4	80	262
1444816	11	13/30	18	0,71	10	150	25	375	0,18	0,12	70	2,8	80	262
1444824	13	1/2	25	0,99	10	150	25	375	0,41	0,27	100	3,9	60	200



EN

Extruded hose for brake systems

Standards: DIN 74310.

Application: used as flexible joint in automotive air brake systems. Suitable for compressed air with oil traces.

Temperature: from -40°C (-40°F) to +70°C (+158°F).

Construction

Tube: black, seamless synthetic rubber compound.

Reinforcement: high strength synthetic fabrics.

Cover: black, seamless, synthetic rubber compound abrasion, ageing, ozone, and weather-resistant.

Branding: IVG AIR BRAKE DIN 74310 – SIZE - QUARTER / YEAR - BATCH PRODUCTION NUMBER.

CN

汽车刹车管

质量标准: 符合DIN 74310

应用范围: 挤出型, 汽车制动软管, 应用于汽车刹车系统中的柔性连接

温度范围: -40° C (-40° F) 到 +70° C (+158° F)

软管结构

内层: 黑色, 无缝, EPDM 橡胶

加强层: 高强度纤维编织

外层: 蓝色, 无缝, 耐磨EPDM 橡胶, 耐臭氧, 耐气候, 耐磨, 耐老化

商标: IVG AIR BRAKE DIN 74310 - 尺寸 - 生产年份/ 周次 - 批次号

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).