



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1420186	51	2	69	2,72	10	150	30	450	1,77	1,19	120	400
1425005	63,5	2-1/2	82	3,23	10	150	30	450	2,26	1,52	120	400
1429655	76	3	94	3,70	10	150	30	450	2,51	1,69	120	400



EN

## Hot air blower hose from compressor to tank

**Application:** softwall hose designed for conveying hot, dry air from compressor to tank truck.

**Temperature:** it resists from -40°C to +200°C with peaks up to 240°C. High temp. can reduce the service life.

**Construction**

**Tube:** white, smooth, EPR rubber, heat resistant.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth (wrapped finish), EPDM rubber, weathering and ozone resistant.

**Branding:** continuous white stripe "IVG Truck (family logo)...".

**Also available upon request:** 1. Different diameters 2. Sahara 240°C with black tube and cover 3. Sahara bd 240°C with white rubber tube and blue cover.

CN

## 热空气输送管240° C

**应用范围:** 软壁胶管，用于从压缩机传送干燥的热空气到罐车  
**温度范围:** 耐受温度范围-40° C 到+200° C，可耐受峰值温度高达 240° C。高温会缩短管道的使用寿命。

**软管结构**

**内层:** 白色，光滑，EPR橡胶，耐热

**加强层:** 高强度合成线

**外层:** 黑色，光滑（表面布纹）EPDM橡胶，耐侵蚀，抗氧化

**商标:** 连续白色商标带“IVG Truck（公司商标）...”

**可选择项:** 1. 不同口径 2. Sahara 240° C，黑色内外层，  
 3. Sahara bd 240° C，白色内胶，蓝色外层