



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1453823	25	1	38	1,50	16	240	64	960	0,94	0,63	150	5,9	0,9	120	400
1454650	32	1-1/4	45	1,77	16	240	64	960	1,14	0,76	175	6,9	0,9	120	400
1454455	38	1-1/2	52	2,05	16	240	64	960	1,43	0,96	225	8,9	0,9	120	400
1450026	50	1-31/32	65,5	2,58	16	240	64	960	2,03	1,36	275	10,8	0,9	120	400
1455133	63,5	2-1/2	78,5	3,09	16	240	64	960	2,58	1,73	300	11,8	0,9	120	400
1453998	75	2-61/64	90	3,55	16	240	64	960	3,08	2,07	350	13,8	0,9	120	400
1457012	100	3-15/16	116	4,57	16	240	64	960	4,40	2,95	450	17,7	0,9	120	400



EN

Fuel and oil suction and delivery hose

Standards: EN 12115:21 (16 bar), EN 1761 (10 bar), ISO 2929 (10 bar), TRbF.

Application: hardwall hose used for the suction delivery of unleaded gasoline and fuels with aromatic content up to 50%, suitable for use as a tank truck or tank wagon hose.

Hose suitable for use in an ATEX environment. Tested by the notified body INERIS.

Temperature: -30°C(-22°F) +90°C(+194°F), w/peaks 110°C(230°F).

Construction

Tube: black, smooth, NBR1 conductive rubber.

Reinforcement: high strength synthetic cord plus steel helix wire.

Cover: black, smooth (wrapped finish), conductive, synthetic rubber, weathering, abrasion, ozone and oil resistant.

Electrical Resistance: Ω/T, electrically conductive hose. Electrical resistance guaranteed for lengths equal or lower than 40m.

Branding: continuous embossed marking according to one of above standards + continuous yellow brand "IVG Oil (family logo)...".

CN

重型油罐车燃料吸排管

质量标准: EN 12115:21 (16 bar), EN 1761 (10 bar), ISO 2929 (10bar), TRbF.

应用范围: 硬壁胶管, 用于吸送和输送无铅汽油和芳烃含量高达50%的燃料。适用于油罐车或油槽车。管道适用于ATEX环境, 经指定机构INERIS测试。

温度范围: -30°C(-22°F) +90°C(+194°F), 瞬时温度可达+110°C(+230°F)。

软管结构

内层: 黑色, 光滑, NBR1导电。

加强层: 高强度合成线绳及螺旋缠绕钢丝

外层: 黑色, 光滑(表面布纹), 导电橡胶, 耐气候, 耐磨损, 耐臭氧和耐油。

电阻性: Ω/T, 导电。长度等于或低于40米的电阻。

商标: 浮体刻印所符合的标准+连续黄色商标带 "IVG Oil (公司商标)...".