



inside diameter		outside diameter		burst pressure		weight nominal		length max	
mm	inch	mm	inch	bar	psi	kg/m	lbs/ft	m	ft
19	3/4	29	1,14	2,5	38	0,44	0,30	120	400
38	1-1/2	48	1,89	2,5	38	0,79	0,53	120	400
51	2	61	2,40	2,5	38	1,03	0,69	120	400
76	3	86	3,39	2,5	38	1,47	0,99	120	400
102	4	114,5	4,51	2,5	38	2,40	1,61	120	400
130	5-1/8	146	5,75	2,5	38	3,76	2,53	120	400
152	6	168	6,62	2,5	38	4,36	2,93	120	400
160	6-19/64	176	6,93	2,5	38	4,58	3,08	120	400
182	7-11/64	202	7,96	2,5	38	6,75	4,54	120	400
203	8	223	8,79	2,5	38	7,50	5,04	120	400
254	10	274	10,80	2,5	38	9,28	6,24	120	400
300	11-13/16	321	12,65	2,5	38	10,98	7,38	120	400
450	17-23/32	472	18,60	2,5	38	17,62	11,84	120	400



EN

Marine wet exhaust gas hose

Standards: ISO 13363:16 type 1B. SAE J 2006:13 type R1. RINA and Lloyd's approved.

Application: softwall rubber hose used for gas exhaust mixed with sea water used in pleasure boats up to 24m length.

Temperature: from -30°C (-22°F) to +100°C(+212°F).

Construction

Tube: black, smooth, synthetic rubber, gas exhaust resistant.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish) synthetic rubber, oil, weathering, and abrasion resistant.

Branding: continuous red stripe. IVG BOAT AMALFI CORD MARINE WET EXHAUST B.P. 2,5 bar 37,5 psi -30°C+100°C -22°F+212°F RINA N° DIP437423CS/001 ISO 13363:16 1B LLOYD'S LR2003044TA SAE J 2006:13 R1 I.D. M/Y.

CN

软壁游艇排气管

质量标准: ISO 13363:04 type 1B. SAE J 2006:03 type R1. RINA 及Lloyd's 劳氏认证。

应用范围: 软壁胶管，用于24 米以下游艇排放气体及海水混合物。

温度范围: -30° C (-22° F) 到 +100° C(+212° F)。

软管结构

内层: 黑色，光滑合成橡胶，耐气体排放。

加强层: 高强度合成线。

外层: 黑色，光滑（表面布纹），合成橡胶，耐油，耐气候，耐磨。

商标: 连续红色条纹:IVG BOAT AMALFI CORD MARINE WET EXHAUST B.P. 2,5 bar 37,5 psi -30° C+100° C -22° F+212° F RINA DIP437423CS/001 ISO 13363:04 1B LLOYD' S LR-2003044TA SAE J 2006:03 R1 I.D. M/Y.