




code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
1436880	16	5/8	24	0,95	3	45	9	135	0,36	0,24	50	2,0	120	400
1436520	19	3/4	27	1,06	3	45	9	135	0,41	0,27	60	2,4	120	400
1436465	25	1	33	1,30	3	45	9	135	0,51	0,34	75	3,0	120	400
1441710	30	1-3/16	38	1,50	3	45	9	135	0,59	0,40	105	4,1	120	400
1435469	38	1-1/2	46,5	1,83	3	45	9	135	0,83	0,56	150	5,9	120	400


EN

Pleasure boat sanitary hose

Standards: EN ISO 8099.

Application: hardwall flexible hose designed to convey water used for water supply and sanitary connections in boats. Completely odourless, and odor impermeable. "The hose is guaranteed for at least 5 years against permeation of smells".

Temperature: from -30°C (-22°F) to +100°C (+212°F).

Construction

Tube: white, smooth, synthetic rubber, completely odourless and odor impermeable.

Reinforcement: high strength synthetic cord plus steel helix wire.

Cover: white, smooth (wrapped finish), synthetic rubber, resistant to sea agents.

Branding: continuous red stripe "SANITARY EN ISO 8099 - ODOURLESS (IVG LOGO)".

Also available upon request: 1. Different diameters.

CN

游艇卫生管

质量标准: EN ISO 8099.

应用范围: 硬壁胶管，用于游艇卫生间供水系统及下水系统输送水，完全无臭无味并防止气味渗透。确保5年以上无气味渗透。

温度范围: -30° C (-22° F) 到 +100° C (+212° F)。

软管结构

内层: 白色，光滑合成橡胶，完全无气味，并防气味渗透。

加强层: 高强度合成线及螺旋钢丝加强。

外层: 白色，光滑（表面布纹），合成橡胶，耐海水。

商标: 连续红色条纹“SANITARY EN ISO 8099 - ODOURLESS (IVG 商标)”。

可选择项: 1. 不同口径。

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, IVG Colbachini SpA cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).