



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1481266	102	4	130	5,12	20	300	80	1200	5,41	3,63	120	400
1481274	127	5	157	6,19	20	300	80	1200	7,00	4,70	120	400



**EN**

## Discharge of abrasive materials

**Standards:** PDA ABS Nr. 23-2375199-PDA.

**Application:** softwall hose designed to convey barite and bentonite and other abrasive materials from ship to oil rigs to consolidate the oil well.

Tensile breaking load: 7000 kgf.

**Temperature:** from -25°C (-13°F) to +70°C (+158°F).

**Construction**

**Tube:** black, smooth, abrasion resistant NR/SBR rubber.

**Reinforcement:** high strength synthetic cord plus antistatic copper wire.

**Cover:** black, smooth (wrapped finish) EPDM rubber, weathering, ozone, and sea-water resistant.

**Branding:** continuous red stripe "IVG Offshore (family logo) - PL ABRASIVE 20 - PDA Nr. 23-2375199-PDA". Embossed marking "IVG Offshore - M/Y - PL ABRASIVE 20 - I.D. - W.P. - TEMP".

**CN**

## 石油平台磨料管

**质量标准:** 输送磨料标准符合PDA ABS Nr. 23-2375199-PDA。

**应用范围:** 软壁软管，设计用于将重晶石和膨润土及其他磨料从船运送到石油钻机，以巩固油井。

抗拉强度：7000kgf。

**温度范围:** 从-25° C到 +70° C。

**软管结构**

**内层:** 黑色，光滑，耐磨的 NR/SBR橡胶。

**加强层:** 高强度合成线加上抗静电铜线。

**外层:** 黑色，光滑（表面布纹）EPDM橡胶，耐气候，耐臭氧和海水。

**商标:** 连续红色条纹带“ IVG Offshore (公司商标) -PL ABRASIVE 20-PDA Nr. 23-2375199-PDA”。连续凸起标记“ IVG Offshore-月 / 年-PL ABRASIVE 20-内径 -工作压力 -温度。”