

Boatex LL

Water and wet exhaust suction and delivery hose





Application:

hardwall hose used for the suction and delivery of water and wet exhaust in pleasure boats.

Long lifespan Wide range of diameters Excellent bending radius

SAE J 2006 type R2.



Tube: black, smooth, synthetic rubber.

Reinforcement:

high strength synthetic cord.

Cover:

black, smooth (wrapped finish), synthetic rubber, weathering resistant.

Temperature: from -30°C (-22°F) to +80°C (+176°F).







Boatex LL



Code	Inside diameter		Outside diameter		Working pressure		Burst pressure		Weight nominal		Bending radius		Length max	
1168193	25	1	34,5	1,36	3	45	9	135	0,65	0,44	95	3,7	120	400
1168215	32	1-1/4	41,5	1,64	3	45	9	135	0,85	0,57	125	4,9	120	400
1168240	38	1-1/2	47,5	1,87	3	45	9	135	0,98	0,66	150	5,9	120	400
1168266	51	2	61	2,40	3	45	9	135	1,35	0,91	205	8,1	120	400
1168290	63,5	2-1/2	74	2,92	3	45	9	135	1,64	1,10	275	10,8	120	400
1156942	76	3	90	3,55	3	45	9	135	2,65	1,78	335	13,2	120	400
1167928	102	4	118	4,65	3	45	9	135	4,42	2,97	475	18,7	120	400

06/08/24 - Above technical data are referring to applications at room temperature (+20°C). IVG Colbachini is not liable for the use that differs from what is confirmed in their catalogues, product sheets, offers, order confirmations and contained recommendations. For a correct use refer to "Recommendations for the selection, storage, use and maintenance of rubber hoses" by Assogomma, available on www.ivgspa.it. With the aim to improve the product, IVG reserves the right to modify the hose specifications without giving any prior notice.

SPECIAL DETAILS

SAFETY INFORMATION - USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on <u>www.ivgspa.it</u>. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).