



Ontario light

Flexible ducting hose for ventilation



Application:

hardwall corrugated hose, extremely light and flexible, suitable for ventilation and ducting.

For ventilation

Very lightweight and flexible

Hardwall with corrugated cover

Tube:

black, smooth, NR/SBR rubber.

Reinforcement:

high strength synthetic cord and helix wire.

Cover:


black, corrugated (wrapped finish), SBR rubber.

Temperature:


from -20°C (-4°F) to +70°C (+158°F).

Branding:

continuous blue stripe "IVG Vent (Family Logo)...".



Ontario light



Code	Inside diameter		Weight nominal		Bending radius		Vacuum	Length max	
	mm	inch	kg/m	lbs/ft	mm	inch		bar	m
1095838	40	1-37/64	0,43	0,29	115	4,5	0,3	60	200
1075250	51	2	0,54	0,36	145	5,7	0,3	60	200
1121375	60	2-3/8	0,63	0,42	180	7,1	0,3	60	200
1100602	70	2-3/4	0,73	0,49	220	8,7	0,2	60	200
1095854	76	3	0,79	0,53	240	9,5	0,2	60	200
1074601	102	4	1,04	0,71	345	13,6	0,2	12	40

SPECIAL DETAILS

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).