

# Coolingflex

## High voltage cable protection and cooling hose for electric arc furnaces





#### Application:

softwall hose used to cool and protect high voltage electrical cables in steel mills, glass works, electric furnaces and in all applications where a hose must be resistant to radiant heat and splashes of white-hot metal.

High Temperature resistant
Flame retardant
Nomex<sup>®</sup> fabric between the reinforcements

#### Tube:

black, smooth, insulating NR/BR rubber.

#### Reinforcement:

high strength synthetic cord plus heat resistant nomex<sup>®</sup> fabric.

#### Cover:

black, smooth (wrapped finish), CR rubber, heat resistant and flame retardant.

#### Temperature:

from -40°C (-40°F) to +80°C (+176°F).

#### Branding:

continuous blue stripe "IVG Cable (family logo)...".





## Coolingflex



Code	Inside diameter		Outside diameter		Working pressure		Burst pressure		Weight nominal		Length max	
1328760	127	5	169	6,66	6	90	30	450	11,58	7,77	60	200
1319400	152	6	199	7,84	6	90	30	450	15,65	10,50	60	200
1362720	170	6-11/160	217	8,55	6	90	30	450	17,26	11,57	60	200
1320718	203	8	253	9,97	6	90	30	450	20,5	13,82	60	200

#### Variants available on request:

- 1.Different diameters.
- 2.Different working pressures.- For this type of application, there are also other hoses available with different structures and specific rubber. Contact IVG to identify the correct product which may bestsuits the required application.



### **SPECIAL DETAILS**

#### SAFETY INFORMATION - USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on <a href="www.ivgspa.it">www.ivgspa.it</a>. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

#### For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).