

# Vinoflex Easy



Non fatty foods. Thermoplastic cover. EASYSHELL SYSTEM




**Application:**

hardwall corrugated hose, lightweight and flexible, for the suction and delivery of vintage wines and alcohols at 96°. Low friction cover.

Low coefficient of friction  
 EasyShell system  
 The best seller for wine

**Specifications:**

Bisphenol A free. BfR XXI Cat.2 for foods D.M. 21/03/73 aqueous and alcohol up to 96% vol. FDA tit.21 art.177.2600 aqueous foods. Phthalates free (REACH Reg.). PAHs free (acc. to ZEK 01.4-08 Cat. 1). Heavy metal tested. Reg. EC 1935/2004. Reg. EC 2023/2006.



**Tube:**

white, smooth, food quality, taste free and odourless IIR rubber. Contains no phthalates.

**Reinforcement:**

high strength synthetic cord plus steel helix wire.

**Cover:**

red, corrugated, translucent thermoplastic material with low friction coefficient, weathering resistant.

**Temperature:**

from -40°C (-40°F) to +120°C (+248°F).

**Branding:**

continuous blues/white stripe "IVG Food...".



# Vinoflex Easy



Code	Inside diameter		Working pressure		Burst pressure		Weight nominal		Bending radius		Vacuum	Length max	
	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch		bar	m
1443062	25	1	10	150	30	450	0,66	0,44	75	3,0	0,6	60	200
1443054	32	1-1/4	10	150	30	450	0,86	0,57	95	3,7	0,6	60	200
1443160	38	1-1/2	10	150	30	450	1,13	0,75	115	4,5	0,6	60	200
1455214	40	1-37/64	10	150	30	450	1,18	0,79	120	4,7	0,6	60	200
1443151	51	1-31/32	10	150	30	450	1,45	0,97	150	5,9	0,6	60	200
1452517	60	2-3/8	10	150	30	450	1,68	1,12	180	7,1	0,6	60	200
1451944	63,5	2-1/2	10	150	30	450	1,77	1,18	195	7,7	0,6	60	200
1450859	76	3	10	150	30	450	2,19	1,46	225	8,9	0,6	60	200
1452444	80	3-5/32	10	150	30	450	2,29	1,53	240	9,5	0,6	60	200
1452452	100	3-15/16	10	150	30	450	2,87	1,94	350	13,8	0,6	60	200

**Variants available on request:**

1. Tube in NR rubber.
2. Cover in different colours.

**Recommended Couplings:**



EasyShell clamps



Garolla



Food coupling DIN 11851

## SPECIAL DETAILS

### SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on [www.ivgspa.it](http://www.ivgspa.it). These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

**For safety reasons, never exceed the working pressure indicated in the product data sheet.**

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department ([marketing@ivgspa.it](mailto:marketing@ivgspa.it)).