



Chicago ASTM

Пожарный рукав для подачи огнетушительных жидкостей, легко накручивается на барабан





Нормативно-правовые акты:

огнестойкое покрытие в соответствии с ASTM C-542.

Применение:

напорный рукав для воды и огнетушительных жидкостей, предназначен для намотки на барабан пожарной мотопомпы, прочный и гибкий, с огнеустойким покрытием.

не распространяющее горение покрытие Долгосрочность максимальная длина до 120м



Внутренний слой:

черный, гладкий, из синтетического каучука.

Усиление:

высокопрочный синтетический корд.

Покрытие:

черное, гладкое (с отпечатком текстильного бандажа), из огнестойкого синтетического каучука CR, устойчивое к атмосферным воздействиям, маслам и к истиранию.

Температура:

от -40°C до +70°C.

Маркировка:

красная маркировочная лента "IVG Fire (логотип сферы применения)...".





Chicago ASTM



Код	Внутренний диаметр		Внешний диаметр		Рабочее давление		Разрывное давление		Номинальный вес		Минимальный Диаметр барабана		Максимальная длина	
1393820	10	25/64	18	0,71	40	600	120	1800	0,21	0,14	200	7,9	120	400
1404164	13	1/2	21	0,83	40	600	120	1800	0,27	0,18	220	8,7	120	400
1409581	19	3/4	30	1,18	40	600	120	1800	0,53	0,36	240	9,5	120	400
1410652	25	1	37	1,46	40	600	120	1800	0,72	0,47	260	10,2	120	400

Возможные варианты по запросу:

1.Другие диаметры.



SPECIAL DETAILS

SAFETY INFORMATION - USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).