


Victoria Premium

Рукав для пара до +210°C



Применение:

напорный рукав с металлокордом для насыщенного пара под давлением до 18 бар, используется в химической, нефтехимической и др. отраслях промышленности. Не рекомендуется для парочистных установок. Может применяться для перегретого пара при пиках до +230°C и 18 бар. Внимание: подача перегретого пара сокращает срок службы рукава. Для увеличения срока службы рекомендуем обеспечивать отток остаточной воды после каждого применения.

красное с покрытием с микроперфорацией
максимальная длина до 120м
для пара до +210°C

Внутренний слой:

черный, гладкий, из устойчивого к насыщенному пару синтетического каучука IIR.

Усиление:

слои металлокорда.

Покрытие:


красное, гладкое с микроперфорацией (с отпечатком текстильного биндажа), из теплостойкого и износостойкого синтетического каучука EPDM, устойчивое к атмосферным воздействиям и истиранию.

Температура:

от -40°C до +210°C.

Маркировка:

тисненая маркировка "IVG Steam Victoria...".



Victoria Premium



Код	Внутренний диаметр		Внешний диаметр		Рабочее давление		Разрывное давление		Номинальный вес		Максимальная длина	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1423754	13	1/2	25	0,99	18	270	180	2700	0,52	0,34	120	400
1424831	19	3/4	31	1,22	18	270	180	2700	0,68	0,45	120	400
1416073	25	1	37	1,46	18	270	180	2700	0,91	0,61	120	400
1420909	51	2	65	2,56	18	270	180	2700	2,12	1,44	120	400

Возможные варианты по запросу:

1. Другие диаметры.

Рекомендуемые соединения:



Steam coupling with clamp

SPECIAL DETAILS

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).