



# **Boatex LO**

### Water and wet exhaust suction and delivery hose





#### Application:

hardwall, semi-corrugated hose used to convey water and wet exhaust in pleasure boats.

Long lifespan Wide range of diameters Excellent bending radius

#### Specifications:

SAE J 2006 type R2.



#### Tube:

black, smooth, synthetic rubber.

#### Reinforcement:

high strength synthetic cord and steel helix wire.

#### Cover:

black, semi-corrugated (wrapped finish), synthetic rubber, weathering resistant.

#### Temperature:

from -30°C (-22°F) to +80°C (+176°F).





## **Boatex LO**



Code		Inside diameter		Outside diameter		Working pressure		Burst pressure		Weight nominal		Bending radius		Length max	
1355554	51	2	61	2,40	3	45	9	135	1,16	0,78	165	6,5	60	200	
1355546	63,5	2-1/2	74	2,92	3	45	9	135	1,47	0,99	215	8,5	60	200	
1299301	76	3	86,5	3,41	3	45	9	135	1,73	1,16	270	10,6	60	200	
1336657	102	4	114	4,49	3	45	9	135	2,8	1,88	385	15,2	60	200	



### **SPECIAL DETAILS**

#### SAFETY INFORMATION - USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on <a href="www.ivgspa.it">www.ivgspa.it</a>. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

#### For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).