


# Vinoflex Easy



**Напорно-всасывающий рукав для нежирных пищевых продуктов. Полимерное покрытие. Система EASYSHELL**




**Применение:**

легкая гофрированная спиральная трубка для изысканных вин и 96° спирта. Покрытие с низким коэффициентом трения.

низкий коэффициент трения  
 самый продаваемый для вина  
 система EasyShell

**Нормативно-правовые акты:**

Без бисфенола А. BfR XXI Cat.2 пищевые. D.M. 21/03/73 пищевые жидкие с содержанием алкоголя до 96% . FDA tit.21 art.177.2600 жидкие пищевые. Не содержит фталатов (REACHReg.). Без IPA (соотв. ZEK 01.4-08 Кат. 1). Тестирован на тяжелые металлы. Reg. EC 1935/2004. Reg. EC 2023/2006.



**Внутренний слой:**

белый, гладкий, из синтетического каучука IIR пищевого качества, без привкуса и запаха.

**Усиление:**

высокопрочный синтетический корд, встроенная стальная спираль.

**Покрытие:**


красный волнистый, изготовлен из термопластичного материала, устойчивого к воздействию атмосферных факторов.

**Температура:**

от -40°C до +120°C.

**Маркировка:**

синий-белая маркировочная лента "IVG Food (логотип сферы применения)...".



# Vinoflex Easy



Код	Внутренний диаметр		Рабочее давление		Разрывное давление		Номинальный вес		Радиус изгиба		Вакуум	Максимальная длина	
	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch		bar	m
1443062	25	1	10	150	30	450	0,66	0,44	75	3,0	0,6	60	200
1443054	32	1-1/4	10	150	30	450	0,86	0,57	95	3,7	0,6	60	200
1443160	38	1-1/2	10	150	30	450	1,13	0,75	115	4,5	0,6	60	200
1455214	40	1-37/64	10	150	30	450	1,18	0,79	120	4,7	0,6	60	200
1443151	51	1-31/32	10	150	30	450	1,45	0,97	150	5,9	0,6	60	200
1452517	60	2-3/8	10	150	30	450	1,68	1,12	180	7,1	0,6	60	200
1451944	63,5	2-1/2	10	150	30	450	1,77	1,18	195	7,7	0,6	60	200
1450859	76	3	10	150	30	450	2,19	1,46	225	8,9	0,6	60	200
1452444	80	3-5/32	10	150	30	450	2,29	1,53	240	9,5	0,6	60	200
1452452	100	3-15/16	10	150	30	450	2,87	1,94	350	13,8	0,6	60	200

## Возможные варианты по запросу:

1. Версия с внутренним слоем из NR.
2. Покрытие других цветов.

## Рекомендуемые соединения:



EasyShell clamps



Garolla



Food coupling DIN 11851

## SPECIAL DETAILS

### SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on [www.ivgspa.it](http://www.ivgspa.it). These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

**For safety reasons, never exceed the working pressure indicated in the product data sheet.**

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department ([marketing@ivgspa.it](mailto:marketing@ivgspa.it)).