

Pippurn

Рукав для всасывания абразивных материалов



Применение:

гофрированный гибкий рукав, предназначен для всасывания песка, гальки, цемента и других абразивных материалов.

Предназначен для очистных систем после пескоструйных работ.

супергибкий

Гибкий и легкий в использовании
конструкция для уборки после пескоструйных
работ

Внутренний слой:

чёрный, гладкий из натурального каучука.

Усиление:

высокопрочный синтетический корд,
встроенные стальная спираль и
антистатическая медная стренга.

Покрытие:


чёрное, гофрированное (с отпечатком
текстильного бандажа) из смеси
синтетического и натурального каучука
NR/SBR, устойчивое к атмосферным
воздействиям и истиранию.

Температура:

от -30°C до +70°C.

Маркировка:

красная маркировочная лента (логотип сферы
применения)...".



Pippurn



Код	Внутренний диаметр		Рабочее давление		Разрывное давление		Номинальный вес		Радиус изгиба		Вакуум	Максимальная длина	
	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch		m	ft
1211412	51	2	3	45	9	135	1,61	1,09	170	6,7	0,9	60	200
1205471	63,5	2-1/2	3	45	9	135	2,18	1,48	210	8,3	0,9	60	200
1205463	76	3	3	45	9	135	2,55	1,73	270	10,6	0,9	60	200
1202294	102	4	3	45	9	135	3,49	2,36	385	15,2	0,9	60	200
1208217	114	4-31/64	3	45	9	135	4,24	2,86	480	18,9	0,8	60	200
1211242	127	5	3	45	9	135	4,95	3,35	520	20,5	0,8	60	200
1207806	152	6	3	45	9	135	7,06	4,74	670	26,4	0,8	60	200
1227459	203	8	2	30	6	90	9,44	6,37	1000	39,4	0,7	60	200

Возможные варианты по запросу:

1. Другие диаметры.
2. Варсия внутреннего слоя из чёрного натурального каучука.

Рекомендуемые соединения:



Camlock



Irrig type CP



Sandblasting

SPECIAL DETAILS

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgsa.it. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgsa.it).