



# Hawk

Pneumatic brake connection EN 45545 HL2, temperature down to -40°C (-40°F). Halogen free.





### Specifications:

EN 45545-2:2015 HL2 R22 and R23.

## Application:

robust flexible hose for compressed air, designed for pneumatic braking systems in rail carriages and locomotives. Fire resistant, with really low toxicity and smoke emission, halogen free, it resists to ballast projections. Supplied in application lengths with tapered ends.

#### Flexible

According to EN 45545-2 HL2 R22 and R23 Fire resistant, halogen free



#### Tube:

black, smooth, synthetic rubber.

### Reinforcement:

high strength synthetic cord.

#### Cover:

black, smooth (wrapped finish), long lasting rubber, weathering and ozone resistant.

## Temperature:

-40°C (-40°F) up to +90°C (+194°F).

### Branding:

embossed and/or coloured marking according to technical specification.





## Hawk



Code	Inside diameter		Outside diameter		Burst pressure		Weight nominal		Bending radius		Length max	
1478117	28	1-7/64	44	1,73	70	1050	1,11	0,75	280	11,0	60	200

### Variants available on request:

- 1.Different diameters.
- 2. With rail couplings.
- 3.According to specific technical standards (UIC 830-I, EN 15807, NF 11380, etc.).



## **SPECIAL DETAILS**

#### SAFETY INFORMATION - USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on <a href="www.ivgspa.it">www.ivgspa.it</a>. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

### For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).