


# Manitoba EN ISO 6134

Рукав для пара до +165°C



**Нормативно-правовые акты:**  
EN ISO 6134:2017 тип 1 класс А.

**Применение:**

напорный рукав для пара, с текстильным кордом, предназначен для насыщенного пара под давлением до 6 бар. Для увеличения срока службы рекомендуется обеспечивать отток остаточной воды после каждого применения.

в соответствии с EN ISO 6134/17 type 1 classe A  
максимальная длина до 120м  
для пара до +165°C



**Внутренний слой:**

черный, гладкий, из устойчивого к пару синтетического каучука EPDM.

**Усиление:**

высокопрочный синтетический корд.

**Покрытие:**


черное, гладкое (с отпечатком текстильного бандаж), из синтетического термостойкого каучука EPDM, устойчивое к атмосферным воздействиям и озону.

**Температура:**

от -40°C до +165°C.

**Маркировка:**

непрерывная тисненая маркировка "IVG - EN ISO 6134:2017 - 1A - STEAM - 6 bar - 165°C - D.I. - M - квартал и год изготовления".



# Manitoba EN ISO 6134



Код	Внутренний диаметр		Внешний диаметр		Рабочее давление		Разрывное давление		Номинальный вес		Максимальная длина	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1421832	10	25/64	21,5	0,85	6	90	60	900	0,31	0,21	120	400
1421859	13	1/2	25	0,99	6	90	60	900	0,37	0,25	120	400
1421840	16	5/8	30	1,18	6	90	60	900	0,55	0,37	120	400
1430130	19	3/4	33	1,30	6	90	60	900	0,62	0,42	120	400
1431366	25	1	40	1,58	6	90	60	900	0,77	0,52	120	400

### Возможные варианты по запросу:

1. Другие диаметры
2. Покрытие других цветов.

### Рекомендуемые соединения:



Steam coupling with clamp

## SPECIAL DETAILS

### SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on [www.ivgspa.it](http://www.ivgspa.it). These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

**For safety reasons, never exceed the working pressure indicated in the product data sheet.**

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department ([marketing@ivgspa.it](mailto:marketing@ivgspa.it)).