

Cable

Рукав для защиты электрокабеля



Применение:

легкий мягкостенный рукав для защиты электрокабеля, применяется на промышленном оборудовании и на сварочных установках.

применение в промышленности для сварочных аппаратов
Экструдированный рукав

Усиление:

прорезиненная синтетическая ткань.

Покрытие:

чёрное, гладкое (с отпечатком текстильного бандажа), из синтетического каучука SBR.

Температура:

от -30°C до +80°C.

Cable



Код	Внутренний диаметр		Внешний диаметр		Номинальный вес		Максимальная длина	
	mm	inch	mm	inch	kg/m	lbs/ft	m	ft
1187821	20	25/32	22	0,87	0,08	0,06	40	131
1112635	22	7/8	24	0,95	0,08	0,05	40	131
1133829	25	1	27	1,06	0,1	0,07	40	131
1111515	28	1-7/64	30	1,18	0,1	0,07	40	131
1112627	30	1-3/16	32	1,26	0,12	0,08	40	131
1212745	35	1-3/8	37	1,46	0,14	0,09	40	131
1272934	38	1-1/2	40	1,58	0,15	0,10	40	131
1131257	40	1-37/64	42	1,65	0,16	0,11	40	131
1191900	45	1-49/64	48	1,89	0,25	0,17	40	131
1307274	51	2	54	2,13	0,24	0,16	40	131
1246160	55	2-11/64	58,5	2,30	0,34	0,23	60	200

Возможные варианты по запросу:

1. Другие диаметры.
2. Cable Isol с теплоизолирующим покрытием.
3. Cable Protection CR из хлоропрена.

SPECIAL DETAILS

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).