

Green carbur cold 10

Экструдированный рукав для различных видов топлива, для использования при низких температурах



Применение:

предназначен для подачи неэтилированного бензина, дизельного топлива, экодизеля, а также для смазочных масел в различных сферах применения. Пригоден для использования при низких температурах.

идеален для низких температур
для бензина без свинца
Экструдированное производство

Внутренний слой:

чёрный, гладкий из токопроводящего синтетического каучука, устойчивый к неэтилированному бензину и к нефтепродуктам с ароматическим содержанием до 50%.

Усиление:

высокопрочное текстильное волокно.

Покрытие:

чёрное, гладкое, из токопроводящего синтетического каучука, устойчивое к нефтепродуктам, атмосферным воздействиям и маслам.

Температура:

от -40°C до +80°C.

Электрическое сопротивление:

внутренний слой $R \leq 1 \times 10^6 \Omega/\text{m}$, покрытие $R \leq 1 \times 10^6 \Omega/\text{m}$.

Маркировка:

IVG RUBBER HOSE GREEN CARBUR COLD 10 BAR
W.P. - SIZE - 50 % Aromatico - BATCH NUMBER.



Green carbur cold 10



Код	Внутренний диаметр		Внешний диаметр		Рабочее давление		Разрывное давление		Номинальный вес		Радиус изгиба		Максимальная длина	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
1451189	6	17/72	13	0,51	10	150	30	450	0,13	0,09	50	2,0	100	328
1452703	8	5/16	15	0,59	10	150	30	450	0,16	0,11	65	2,6	100	328
1451197	10	25/64	17	0,67	10	150	30	450	0,19	0,13	80	3,2	100	328
1451200	13	1/2	20	0,79	10	150	30	450	0,23	0,16	105	4,1	60	200
1452053	15	19/32	23	0,91	10	150	30	450	0,31	0,19	120	4,7	60	200
1449834	19	3/4	27	1,06	10	150	30	450	0,39	0,25	150	5,9	60	200

Рекомендуемые соединения:



Camlock



Camlock EN 14420-7 (DIN 2828)



Fuel Italian Type coupling

SPECIAL DETAILS

SAFETY INFORMATION – USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, **IVG Colbachini** cannot guarantee the proper functioning of the product for all situations.

The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the IVG hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills. IVG Colbachini is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people.

For the selection and proper use of the IVG products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on www.ivgspa.it. These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.

For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover, additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (marketing@ivgspa.it).